

## Trailer - mono axle



CMB65M WITH BALL HOLDER KIT

### Standard equipment:

- quick coupling for lift attachment
- trilateral overturn
- device to avoid bad tipping over
- parachute valve on the piston
- audible warning device during tipping over

- Norm - compliant lighting system
- stiff suspensions
- statement for EC certificate
- documents for road homologation



Code	Tipper External sizes	h. sides	Full load	Square axle	Tyres	Price
CMB20M	1500X2500	400	15-20	45	10.0/75 R15.3 or similar	2.450
CMB30M	1700X2800	400	30	45	10.0/75 R15.3 or similar	2.680
CMB38M	1800X3000	500	38	60	11,5/80R15,3 or similar	3.110
CMB50M	2000X3500	500	50	60	11,5/80R15,3 or similar	3.650
CMB60M	2300X4100	600	60	70	305/70R22,5 half new	4.740
CMB65M	2400X4600	600	60	80	215/75R17,5 twin or 425/55R19,5	6.070
CMB50MS	2000X3500	500	50	60	265/70R19.5 or similar	4.135
CMB60MS	2300X4100	600	60	80	385/55R22.5 or similar	5.215

**CMB MS new model** : thickened frame, parabolic suspension of 8 (50ms) and 10 (60ms) tons, increased axle, body in sheet metal of 4 mm. and reinforced structure, anti-noise rubbers on the frame

### Please note:

- 1) The CMB20M trailer can also be registered for 15 Q. li, but this must be specified when ordering.
- 2) Trailers of 60 q. li have standard hydraulic mixed mechanical brakes
- 3) The CMB65M trailer has the side rails split in half.
- 4) The industrial wheels are semi-new and the measures are not binding.

## PRICES FOR OPTIONAL

<i>Optional</i>	<i>CMB 20M</i>	<i>CMB 30M</i>	<i>CMB 38M</i>	<i>CMB50M CMB50MS</i>	<i>CMB 60M CMB60MS</i>	<i>CMB 65M</i>
upside-down openable sides	340 <b>B0001</b>		385 <b>B0002</b>		415 <b>B0003</b>	450 <b>B0004</b>
<b>B0005</b> exit for the grain on the bank	170					
<b>B0007</b> Hydraulic brake, manual (industrial use)	190			-		
<b>B0008</b> Predisposition for pillars and anterior and posterior pillars	-					940

+ VAT and transport